

ESRTP5

Programmable Room Thermostat

- Delayed Start & TPI Technology
- Includes optional landlord service safety feature
- 7 day, 5/2 day or 24 hour programming options
- Pre-set built in programme
- Select either 4 or 6 time and temperature events
- Automatic BST/GMT 1 hour time change
- Easy to use and quick to install
- Holiday Mode



Programmable Room Thermostat

The sleek and stylish ESRTP5 is a 7 day, 5/2 or 24 hour programmable room thermostat designed to provide automatic time and temperature control of all domestic central heating applications.

The ESRTP5 is easy to install and use, and offers the householder a range of convenient, feature-packed options whilst offering supreme levels of heating control, energy efficiency and comfort.

The ESRTP5 programmable room thermostat with its large LED display, includes many features, making it ideal for situations where a higher flexibility of control is required. This programmable room thermostat provides true 7 day (5/2 day or 24 hour) programming options, with the choice between either four or six time and temperature events selectable available each day. The ESRTP5 comes pre-programmed for ease of use, but the user can create their own individual programme or modify the existing option.

With built in summer/winter changeover, this product eliminates the need for time-setting and BST/GMT time changes. The additional features of TPI and delayed start provide the householder with further opportunities for saving energy, whilst the optional landlord service safety feature offers protection for tenants and landlords against illegal boiler negligence (in compliance with Gas Safety Regulation 36).

Technical Data

Programmable Room Thermostat	ESRTP5
Temperature Control Class	ErP Class IV Product (2%)
Energy Efficiency Technology	TPI (Chrono-proportional) Control, Delayed Start
Programming	7 day, 5/2 day & 24 hour
Power Supply	230VAC
Temperature Adjustment Range	5°C to 35°C
Total Switch Rating	3(1)A
Temperature Sensor Type	+/- 1°C at 20°C
Plastics	Thermoplastic, flame retardant
Protection Rating	IP30
Dimensions	95mm x 95mm x 39mm
Number of events per day	4 or 6 selectable
BST/GMT time change	Automatic
Factory Pre-set programme	Yes
Complies with	EN60730-1 EN60730-2.7, EMC Directive 2014/30/EU, LVD Directive 2014/35/EU



www.esicontrols.co.uk