

ESWC1

# Wiring Centre

## User and Installation Instructions

The ESWC1 Wiring Centre is designed to be a safe and convenient method of system wiring. The ESWC1 provides a safe means of connection whilst reducing installer time by simplifying the wiring and circuit testing, with a dedicated terminal block for each system component. The ESWC1 is suited to all popular heating systems and manufactured in a robust fire retardant ABS.

### Installation

Always isolate the AC mains before installing the wiring centre. Wire the system components to the correct terminals.



| Wiring Centre               |   |
|-----------------------------|---|
| Protection Rating           | IP20  |
| Maximum Ambient Temperature | 55°C  |
| Voltage Rating              | 230V 50/60Hz  |
| Current Rating              | 10A   |
| Fuse Rating                 | 2A 230V 50Hz  |
| Complies With:              | EC Directive 2006/95/EC, EMC (89/336 & 92/32 EEC) BS EN 60730-1:2000 BS EN 60730-2-9:2002. LVD (73/23/EEC) (93/68/EEC) BS EN 60730-1:2000 BS EN 60730-2-9:2000) |

**WARNING: Interference with sealed parts renders the guarantee void. Always isolate the AC mains supply before removing or fitting the product. This accessory must be fitted by a competent person, and installation must comply with the guidance provided in the current editions of BS7671 (IEE wiring regulations) and part 'P' of the building regulations.**

In the interests of continuous product improvement we reserve the right to alter designs, specifications and materials without prior notice and cannot accept liability for errors.