

Wireless and wired programmable room thermostats

Pacific ES RTP4+ & Atlantic ES RTP4RFW



Our programmable room thermostats are cost effective, easy-to-use and are packed with energy saving features. Available in both wired and wireless options, they are suited for use in any domestic heating installation

The wired programmable thermostat is simple-to-use and install. Its LCD screen is backlit, making it easy to programme and control room temperatures. The wireless programmable thermostat removes the need for any fixed wiring between the thermostat and boiler, reducing the installation time even further and the need for any disruption to your customer's home interiors. Both thermostats offer a landlord service interval, making it a perfect choice for social housing.

The ES RTP4RFW can be controlled through the Centro App, Alexa and Google home when installed with a Wi-Fi HUB (sold separately).



ESWIFIHUB

The ESi Wi-Fi Hub is a USB-powered device that transforms ESi compatible controls into smart devices for control via Alexa, google home or the Centro App.

Technical data

Model	ESWIFIHUB
Power Supply	5V USB Adaptor
Frequency	2.4 GHZ
Software	ESi Centro app (see Page 5)

Features & benefits

Features	Benefits
Load compensation via OpenTherm	Saves up to 15% gas use by controlling boiler modulation
Free laser printing	Encourages repeat business from your customer
Optimum start/stop and delayed start	Providing cost savings
7 day, 5/2 day or 24 hour options	To suit your customer's lifestyle
Automatic summer/winter change	For convenience and comfort
4 or 6 events per day	Complete flexibility
Large LCD display	Easy to read temperature and set comfort levels
Battery powered thermostat (with low power indicator)	Quick installation
Auto, manual, all day and holiday modes	Complete control and comfort to suit your customer's needs
Boiler Plus compliant	Meeting required standards
Landlord service interval reminder	Perfect for social housing use
3 year warranty*	Complete peace of mind

*To qualify for the full extended warranty, register your product at www.esicontrols.co.uk. Otherwise, a standard 12-month warranty applies. See our website for full terms and conditions.

Technical data

Model	ES RTP4+	ES RTP4RFW
Battery	2 x AA	2 x AA
Hard-wired (built-in sensor)	✓	-
Wireless (built-in sensor complete with receiver)	-	✓
Power supply	2 x AA or power over OpenTherm**	230V RF Receiver & 2 x AA batteries for the thermostat
Temperature control class	ErP class 5 (3%)	
Programming	7 day, 5/2 day & 24 hour	
Temperature adjustment range	5° C to 35° C	
Energy saving technology	TPI control, Delayed start/stop, optimum start/stop, OpenTherm technology	
Service interval timer	28 to 366 days	
Switching	Suitable for Volt free / Low volt / 230V	
Dimensions	127mm x 81mm x 28mm (w x h x d)	

** With power over OpenTherm, the thermostat can be powered just from the OpenTherm connection with no need for batteries.